





NEEDLE ROLLER BEARINGS

INNER RINGS FOR INCH SERIES DRAWN CUP BEARINGS

- Check for availability.
- Ideal choice when shaft is not practical to use as inner raceway.
- Provided in inch (IR, IRA) nominal dimensions for use with inch series drawn cup bearings.
- Designed to meet established inch tolerances.
- Designed to be wider than matching drawn cup bearing.
- Maximum shaft fillet radius ($r_{a \max}$) cannot exceed inner ring bore chamfer ($r_{s \min}$) as shown.
- Optional centralized lubrication groove (bore) and thru-hole available – specify when ordering.
- Designed to provide a loose transition fit on the shaft and should be axially clamped against a shoulder.



- If a tight transition fit must be used to keep the inner ring from rotating relative to the shaft, the inner ring O.D. must not exceed the raceway diameter for the matching drawn cup bearing after being mounted on the shaft.
- See tables for bearing raceway diameter dimensions.
- After mounting, if O.D. of inner ring exceeds required raceway diameter for matching bearing, ring should be ground to proper diameter while mounted on shaft.
- Unmarked end of inner ring should be assembled against shaft shoulder to assure clearing maximum allowable shaft fillet ($r_{a \max}$) – as indicated in tables shown.

Shaft Dia.	d		F		B		r _s min.	Inner Ring Designation	Mounting Dimensions Transition Fit				Approx. Wt.
	Max.	Min.	Max.	Min.	Max.	Min.	Min.		Loose		Tight		
									Max.	Min.	Max.	Min.	
in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.		mm in.	mm in.	mm in.	mm in.	kg lbs.
3/16	4.826 0.1900	4.813 0.1895	9.525 0.3750	9.512 0.3745	13.61 0.536	13.36 0.526	0.64 0.025	IRA-3	4.818 0.1897	4.806 0.1892	4.829 0.1901	4.816 0.1896	0.005 0.012
1/4	6.350 0.2500	6.337 0.2495	11.113 0.4375	11.100 0.4370	13.61 0.536	13.36 0.526	0.64 0.025	IRA-4	6.342 0.2497	6.330 0.2492	6.353 0.2501	6.340 0.2496	0.006 0.014
5/16	7.938 0.3125	7.925 0.3120	12.700 0.5000	12.687 0.4995	13.61 0.536	13.36 0.526	0.64 0.025	IRA-5	7.930 0.3122	7.917 0.3117	7.940 0.3126	7.927 0.3121	0.008 0.017
3/8	9.525 0.3750	9.512 0.3745	14.288 0.5625	14.275 0.5620	13.08 0.515	12.83 0.505	0.64 0.025	IR-68	9.517 0.3747	9.505 0.3742	9.528 0.3751	9.515 0.3746	0.009 0.019
	9.525 0.3750	9.512 0.3745	14.288 0.5625	14.275 0.5620	19.43 0.765	19.18 0.755	0.64 0.025	IR-612	9.517 0.3747	9.505 0.3742	9.528 0.3751	9.515 0.3746	0.013 0.028
	9.525 0.3750	9.512 0.3745	14.288 0.5625	14.275 0.5620	19.96 0.786	19.71 0.776	0.64 0.025	IRA-6	9.517 0.3747	9.505 0.3742	9.528 0.3751	9.515 0.3746	0.013 0.029
	9.525 0.3750	9.512 0.3745	15.875 0.6250	15.862 0.6245	13.08 0.515	12.83 0.505	0.64 0.025	IR-68-1	9.517 0.3747	9.505 0.3742	9.528 0.3751	9.515 0.3746	0.012 0.027
	9.525 0.3750	9.512 0.3745	15.875 0.6250	15.862 0.6245	19.43 0.765	19.18 0.755	0.64 0.025	IR-612-1	9.517 0.3747	9.505 0.3742	9.528 0.3751	9.515 0.3746	0.018 0.040
7/16	11.113 0.4375	11.100 0.4370	15.875 0.6250	15.862 0.6245	19.96 0.786	19.71 0.776	0.64 0.025	IRA-7	11.105 0.4372	11.092 0.4367	11.115 0.4376	11.102 0.4371	0.015 0.033
1/2	12.700 0.5000	12.687 0.4995	19.050 0.7500	19.037 0.7495	13.08 0.515	12.83 0.505	1.02 0.040	IR-88	12.692 0.4997	12.680 0.4992	12.703 0.5001	12.690 0.4996	0.015 0.033
	12.700 0.5000	12.687 0.4995	19.050 0.7500	19.037 0.7495	19.43 0.765	19.18 0.755	1.02 0.040	IR-812	12.692 0.4997	12.680 0.4992	12.703 0.5001	12.690 0.4996	0.023 0.050

Bore and O.D. tolerance limits correspond to the single mean diameter (the arithmetical mean of the largest and smallest diameters in a single radial plane).

⁽¹⁾ $r_{a \max}$ is equal to minimum inner ring bore chamfer ($r_{s \min}$) at unmarked end.

Shaft Dia.	d		F		B		r _s min.	Inner Ring Designation	Mounting Dimensions Transition Fit				Approx. Wt.
	Max.	Min.	Max.	Min.	Max.	Min.			Loose		Tight		
									Max.	Min.	Max.	Min.	
in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.		mm in.	mm in.	mm in.	mm in.	kg lbs.
1/2	12.700 0.5000	12.687 0.4995	19.050 0.7500	19.037 0.7495	19.96 0.786	19.71 0.776	1.02 0.040	IRA-8	12.692 0.4997	12.680 0.4992	12.703 0.5001	12.690 0.4996	0.023 0.051
5/8	15.875 0.6250	15.862 0.6245	22.225 0.8750	22.212 0.8745	19.43 0.765	19.18 0.755	1.02 0.040	IR-1012	15.867 0.6247	15.855 0.6242	15.878 0.6251	15.865 0.6246	0.027 0.060
	15.875 0.6250	15.862 0.6245	22.225 0.8750	22.212 0.8745	19.96 0.786	19.71 0.776	1.02 0.040	IRA-10	15.867 0.6247	15.855 0.6242	15.878 0.6251	15.865 0.6246	0.028 0.062
3/4	15.875 0.6250	15.862 0.6245	22.225 0.8750	22.212 0.8745	25.78 1.015	25.53 1.005	1.02 0.040	IR-1016	15.867 0.6247	15.855 0.6242	15.878 0.6251	15.865 0.6246	0.036 0.080
	19.050 0.7500	19.037 0.7495	25.400 1.0000	25.387 0.9995	13.08 0.515	12.83 0.505	1.02 0.040	IR-128	19.042 0.7497	19.030 0.7492	19.053 0.7501	19.040 0.7496	0.021 0.047
	19.050 0.7500	19.037 0.7495	25.400 1.0000	25.387 0.9995	19.43 0.765	19.18 0.755	1.02 0.040	IR-1212	19.042 0.7497	19.030 0.7492	19.053 0.7501	19.040 0.7496	0.032 0.070
	19.050 0.7500	19.037 0.7495	25.400 1.0000	25.387 0.9995	25.78 1.015	25.53 1.005	1.02 0.040	IR-1216	19.042 0.7497	19.030 0.7492	19.053 0.7501	19.040 0.7496	0.042 0.093
	19.050 0.7500	19.037 0.7495	25.400 1.0000	25.387 0.9995	26.31 1.036	26.06 1.026	1.02 0.040	IRA-12	19.042 0.7497	19.030 0.7492	19.053 0.7501	19.040 0.7496	0.043 0.095
	19.050 0.7500	19.037 0.7495	25.400 1.0000	25.387 0.9995	32.13 1.265	31.88 1.255	1.02 0.040	IR-1220	19.042 0.7497	19.030 0.7492	19.053 0.7501	19.040 0.7496	0.053 0.116
	19.050 0.7500	19.037 0.7495	25.400 1.0000	25.387 0.9995	38.48 1.515	38.23 1.505	1.02 0.040	IR-1224	19.042 0.7497	19.030 0.7492	19.053 0.7501	19.040 0.7496	0.063 0.139
	20.638 0.8125	20.625 0.8120	25.400 1.0000	25.387 0.9995	19.43 0.765	19.18 0.755	1.02 0.040	IR-1312	20.630 0.8122	20.617 0.8117	20.640 0.8126	20.627 0.8121	0.024 0.054
	20.638 0.8125	20.625 0.8120	25.400 1.0000	25.387 0.9995	25.78 1.015	25.53 1.005	1.02 0.040	IR-1316	20.630 0.8122	20.617 0.8117	20.640 0.8126	20.627 0.8121	0.033 0.072
	22.225 0.8750	22.212 0.8745	28.575 1.1250	28.562 1.1245	25.78 1.015	25.53 1.005	1.02 0.040	IR-1416	22.217 0.8747	22.205 0.8742	22.228 0.8751	22.215 0.8746	0.050 0.111
	22.225 0.8750	22.212 0.8745	28.575 1.1250	28.562 1.1245	26.31 1.036	26.06 1.026	1.02 0.040	IRA-14	22.217 0.8747	22.205 0.8742	22.228 0.8751	22.215 0.8746	0.050 0.111
	23.813 0.9375	23.800 0.9370	28.575 1.1250	28.562 1.1245	25.78 1.015	25.53 1.005	1.02 0.040	IR-1516	23.805 0.9372	23.792 0.9367	23.815 0.9376	23.802 0.9371	0.037 0.082
1	25.400 1.0000	25.387 0.9995	31.750 1.2500	31.737 1.2495	19.43 0.765	19.18 0.755	1.02 0.040	IR-1612	25.392 0.9997	25.380 0.9992	25.403 1.0001	25.390 0.9996	0.041 0.090
	25.400 1.0000	25.387 0.9995	31.750 1.2500	31.737 1.2495	25.78 1.015	25.53 1.005	1.02 0.040	IR-1616	25.392 0.9997	25.380 0.9992	25.403 1.0001	25.390 0.9996	0.057 0.125
	25.400 1.0000	25.387 0.9995	31.750 1.2500	31.737 1.2495	26.31 1.036	26.06 1.026	1.02 0.040	IRA-16	25.392 0.9997	25.380 0.9992	25.403 1.0001	25.390 0.9996	0.056 0.124
	28.575 1.1250	28.562 1.1245	34.925 1.3750	34.912 1.3745	19.43 0.765	19.18 0.755	1.02 0.040	IR-1812	28.567 1.1247	28.555 1.1242	28.578 1.1251	28.565 1.1246	0.045 0.100
	28.575 1.1250	28.562 1.1245	34.925 1.3750	34.912 1.3745	25.78 1.015	25.53 1.005	1.02 0.040	IR-1816	28.567 1.1247	28.555 1.1242	28.578 1.1251	28.565 1.1246	0.060 0.133
	28.575 1.1250	28.562 1.1245	34.925 1.3750	34.912 1.3745	32.13 1.265	31.88 1.255	1.02 0.040	IR-1820	28.567 1.1247	28.555 1.1242	28.578 1.1251	28.565 1.1246	0.075 0.166
1 3/16	30.163 1.1875	30.150 1.1870	38.100 1.5000	38.087 1.4995	25.78 1.015	25.53 1.005	1.02 0.040	IR-1916	30.155 1.1872	30.142 1.1867	30.165 1.1876	30.152 1.1871	0.084 0.186
	30.163 1.1875	30.150 1.1870	38.100 1.5000	38.087 1.4995	32.13 1.265	31.88 1.255	1.02 0.040	IR-1920	30.155 1.1872	30.142 1.1867	30.165 1.1876	30.152 1.1871	0.101 0.223
1 1/4	31.750 1.2500	31.737 1.2495	38.100 1.5000	38.087 1.4995	25.78 1.015	25.53 1.005	1.52 0.060	IR-2016	31.742 1.2497	31.730 1.2492	31.753 1.2501	31.740 1.2496	0.069 0.152
	31.750 1.2500	31.737 1.2495	38.100 1.5000	38.087 1.4995	32.13 1.265	31.88 1.255	1.52 0.060	IR-2020	31.742 1.2497	31.730 1.2492	31.753 1.2501	31.740 1.2496	0.086 0.190

Bore and O.D. tolerance limits correspond to the single mean diameter (the arithmetical mean of the largest and smallest diameters in a single radial plane).


Continued on next page.




NEEDLE ROLLER BEARINGS

INNER RINGS FOR INCH SERIES DRAWN CUP BEARINGS—continued

- Check for availability.
- Ideal choice when shaft is not practical to use as inner raceway.
- Provided in inch (IR, IRA) nominal dimensions for use with inch series drawn cup bearings.
- Designed to meet established inch tolerances.
- Designed to be wider than matching drawn cup bearing.
- Maximum shaft fillet radius ($r_{a \max}$) cannot exceed inner ring bore chamfer ($r_{s \min}$) as shown.
- Optional centralized lubrication groove (bore) and thru-hole available – specify when ordering.
- Designed to provide a loose transition fit on the shaft and should be axially clamped against a shoulder.



- If a tight transition fit must be used to keep the inner ring from rotating relative to the shaft, the inner ring O.D. must not exceed the raceway diameter for the matching drawn cup bearing after being mounted on the shaft.
- See tables for bearing raceway diameter dimensions.
- After mounting, if O.D. of inner ring exceeds required raceway diameter for matching bearing, ring should be ground to proper diameter while mounted on shaft.
- Unmarked end of inner ring should be assembled against shaft shoulder to assure clearing maximum allowable shaft fillet ($r_{a \max}$) – as indicated in tables shown.



Shaft Dia.	d		F		B		r _{s min.}	Inner Ring Designation	Mounting Dimensions Transition Fit				Approx. Wt.
									Loose		Tight		
	Max.	Min.	Max.	Min.	Max.	Min.			Max.	Min.	Max.	Min.	
in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.		mm in.	mm in.	mm in.	mm in.	kg lbs.
1 1/4	31.750 1.2500	31.737 1.2495	38.100 1.5000	38.087 1.4995	32.66 1.286	32.41 1.276	1.52 0.060	IRA-20	31.742 1.2497	31.730 1.2492	31.753 1.2501	31.740 1.2496	0.086 0.190
1 3/8	34.925 1.3750	34.912 1.3745	41.275 1.6250	41.262 1.6245	32.13 1.265	31.88 1.255	1.52 0.060	IR-2220	34.917 1.3747	34.905 1.3742	34.928 1.3751	34.915 1.3746	0.094 0.208
1 7/16	36.513 1.4375	36.500 1.4370	44.450 1.7500	44.437 1.7495	25.78 1.015	25.53 1.005	1.52 0.060	IR-2316	36.505 1.4372	36.492 1.4367	36.515 1.4376	36.502 1.4371	0.100 0.220
	36.513 1.4375	36.500 1.4370	44.450 1.7500	44.437 1.7495	38.48 1.515	38.23 1.505	1.52 0.060	IR-2324	36.505 1.4372	36.492 1.4367	36.515 1.4376	36.502 1.4371	0.150 0.331
1 1/2	38.100 1.5000	38.087 1.4995	44.450 1.7500	44.437 1.7495	25.78 1.015	25.53 1.005	1.52 0.060	IR-2416	38.092 1.4997	38.080 1.4992	38.103 1.5001	38.090 1.4996	0.078 0.173
	38.100 1.5000	38.087 1.4995	44.450 1.7500	44.437 1.7495	38.48 1.515	38.23 1.505	1.52 0.060	IR-2424	38.092 1.4997	38.080 1.4992	38.103 1.5001	38.090 1.4996	0.122 0.270
1 11/16	42.863 1.6875	42.850 1.6870	52.388 2.0625	52.375 2.0620	38.48 1.515	38.23 1.505	1.52 0.060	IR-2724	42.855 1.6872	42.842 1.6867	42.865 1.6876	42.852 1.6871	0.212 0.468
1 3/4	44.450 1.7500	44.437 1.7495	52.388 2.0625	52.375 2.0620	38.48 1.515	38.23 1.505	1.52 0.060	IR-2824	44.442 1.7497	44.430 1.7492	44.453 1.7501	44.440 1.7496	0.180 0.396
1 13/16	46.038 1.8125	46.025 1.8120	52.388 2.0625	52.375 2.0620	25.78 1.015	25.53 1.005	1.52 0.060	IR-2916	46.030 1.8122	46.017 1.8117	46.040 1.8126	46.027 1.8121	0.097 0.214
	46.038 1.8125	46.025 1.8120	52.388 2.0625	52.375 2.0620	38.48 1.515	38.23 1.505	1.52 0.060	IR-2924	46.030 1.8122	46.017 1.8117	46.040 1.8126	46.027 1.8121	0.146 0.322
1 7/8	47.625 1.8750	47.612 1.8745	53.975 2.1250	53.962 2.1245	38.48 1.515	38.23 1.505	1.52 0.060	IR-3024	47.617 1.8747	47.605 1.8742	47.628 1.8751	47.615 1.8746	0.145 0.319
2 1/2	63.500 2.5000	63.487 2.4995	69.850 2.7500	69.837 2.7495	25.78 1.015	25.53 1.005	1.52 0.060	IR-4016	63.495 2.4998	63.477 2.4991	63.505 2.5002	63.487 2.4995	0.132 0.290

Bore and O.D. tolerance limits correspond to the single mean diameter (the arithmetical mean of the largest and smallest diameters in a single radial plane).

⁽¹⁾ $r_{a \max}$ is equal to minimum inner ring bore chamfer ($r_{s \min}$) at unmarked end.